

ABRASAPIPE®

WELD OVERLAY WEAR PIPE

www.alloysint.com.au | sales@alloysint.com.au

25 Raymond Road, Laverton North, VIC, 3026

Phone (03) 8368 2222

AbrasaPipe® is chrome carbide weld-overlay wear pipe. The high hardness of the weld overlay make its suitable for abrasion resistant applications, such as transport of slurries, abrasive minerals and dust.

AbrasaPipe® features significantly better abrasion resistance than epoxy-composite linings, and better impact resistance than ceramic linings. Pipes come in standard sizes and can also be custom made to your application.



Standard Pipe Sizes

mm	Inch	OD	ID	Internal Hardfacing (mm)
63	2.5	73	52	3-5
75	3	89	72	3-6
90	3.5	102	86	3-6
100	4	114	98	3-8
150	6	168	150	3-8
200	8	219	197	4-9
250	10	273	249	4-9
300	12	324	297	4-9

Custom pipe sizes are also available, with multiple layers of hardfacing.

- Internally or externally hardfaced pipe
- Same composition as AbrasaPlate®
- All standard pipe sizes available
- Standard lengths up to 12m
- Smooth overlay
- Elbows, transitions and reducers
- Very small diameters
- Hardfaced joints, flanges or neck rings

